



Length:	7,10 m
Beam:	2,55 m
Draft (hull):	0,50 m
Weight:	1550 kg
Persons:	10
Berths:	2
Engine:	150-250 hp
Category:	C
Deadrise angle:	20 °

Standard equipment

- Internal fuel tank, 227 litres
- Garmin 1223 xsv Touch
- Yamaha electronic remote control device
- Yamaha 5" LAN multidisplay
- Yamaha Y-COP
- Windscreen wipers
- Double battery system
- Teak on cockpit floor
- Canopy & canopy garage
- Folding back rest of navigator's seat
- Cushions, Silvertex Carbon
- Cushion for berth under cockpit
- Integrated fill-in cushion to forward berth
- Cabin carpets
- Sink & pressure water, 39 litres
- Sea water toilet, toilet curtain & holding tank, 47 l
- LED interior lights
- LED navigation lights
- 1 x 12V output & 1 x USB output
- Tube for bow thruster
- Large hull portlights with ventilators
- Large deck skylights
- Fire extinguisher
- Electric bilge pump
- Stainless steel handrails
- S/steel windscreen frame
- 3 anchor boxes
- Swim platform & boarding ladder
- Shoe self
- 2 cup holders
- 4 fender fittings
- 4 fenders, fender covers & ropes
- Flagpole socket
- White hull colour

Extra equipment

- Power steering
- Hydraulic steering
- Yamaha electric steering
- Trim tabs with indicator
- Adjustable steering wheel
- Bow thruster
- Dark steering console
- Sleipner anchor windlass rear
- Maxwell anchor windlass bow
- Drawer fridge, 30 litres
- Galley & Wallas 800D ceramic stove
- Heater 2 kW
- Shore power
- Fusion MS-RA 210 & speakers
- Fusion Premium audio package
- Water skiing bracket
- LED docking lights
- Cockpit table
- Portable fridge, 18 litres
- Electric flush toilet
- Syntek on cockpit floor
- Cockpit tonneau cover
- 2 offshore seats instead of navigator's bench
- Sundeck to cockpit, Carbon or Macadamia
- Cockpit cushions, Macadamia
- Bedspread
- Cabin curtains
- Folding cleats (2)



Test results Yamaha F250

Persons	RPM	Knots	L/h	L/Nm
2	5800	42,2	96,2	2,28
2	5500	40,0	84,4	2,11
2	5000	36,0	68,0	1,89
2	4500	32,2	54,4	1,69
2	4000	28,6	42,7	1,49
2	3500	24,0	32,0	1,33
2	3000	15,4	23,8	1,56

FINNMASTER

Propeller: 6CE - Saltw. II SDS 15 1/2 x 17-M